



Electrical Characteristics :
Insulation Resistance : 500M Ω Min.
Contact Resistance : 30m Ω Max.
Withstand Voltage : 1000 VAC 1 minute.
Current Rating : 1.5A

Material:
Housing : Thermoplastic UL94V-0
Contact : Full Gold Plating
Spring Wire : Dia 0.45mm Phosphor Bronze
Optional Gold Plating Over Nickel
CUL File No : E215573

PART NO : 5 1 A 6 6 - B * 1

Positions	Ports
Contacts	Gold Plated
Housing Color	0 : Gold Flash
	1 : 60 μ "
	2 : 150 μ "
	3 : 30 μ "
	4 : 50 μ "
	B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 51 (SERIES)	TITLE	SIDE ENTRY PCB JACK		UNIT
A	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick		圖名	RJ11 6P6C	mm	
B						PART NO.	51A66-B*1	Inch	
C						REV.		SCALE	
D						版本		比例	
E						日期	2007-01-22	1:1	
						CHECKED BY	Michael	DRAWN BY	
						審核		製圖	
								Valiant	



博 崑 電 子 股 份 有 限 公 司
POWERWAY ELECTRONICS CO.,LTD.