



SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :

- Insulation Resistance : 500M Ω Min.
- Contact Resistance : 30m Ω Max.
- Withstand Voltage : 1000 VAC 1 minute.
- Current Rating : 1.5A

Material:

Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel

PART NO : 5 2 A 4 4 - B * 1



ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 52 (SERIES)
(A)	A.1	Withstand Voltage 500修改为1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm \pm 0.075 mm 0.00 mm \pm 0.15 mm 0.0 mm \pm 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE		SIDE ENTRY PCB JACK		UNIT	mm
圖名		RJ11 4P4C		單位	inch
PART NO.		52A44-B*1		SCALE	1:1
料號				比例	
REV.	日期	DATE	2007-03-07		
版本	A.1	日期			
CHECKED BY	Michael	DRAWN BY	David		
審核		製圖			



博 崑 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.