

SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 3 A 6 6 - B * 1

Positions
 Contacts
 Housing Color


Ports
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

B : Black

| ZONE | REV. | DESCRIPTION | DATE | APPD. |
|------|------|---------------------------------|------------|-------|
| (A) | A.1 | Withstand Voltage 500修改為1000VAC | 2008-08-01 | Nick |
| (B) | | | | |
| (C) | | | | |
| (D) | | | | |
| (E) | | | | |

FILE NO : 53 (SERIES)

TOLERANCE(公差) :
 0.000 mm ± 0.075 mm
 0.00 mm ± 0.15 mm
 0.0 mm ± 0.25 mm

| | | | | | |
|--|-----------|----------|-------------------------|------|---------|
|  博 崙 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD. | | TITLE | RJ11 TOP ENTRY PCB JACK | UNIT | mm |
| | | 圖名 | | 單位 | Inch |
| PART NO. | 53A66-B*1 | SCALE | 1:1 | | |
| 料號 | | 比例 | | | |
| REV. | A.1 | DATE | 2007-03-02 | | |
| 版本 | | 日期 | | | |
| CHECKED BY | Michael | DRAWN BY | | | |
| 審核 | | 製圖 | | | |
| | | | | | Valiant |