



**Electrical Characteristics :**  
 Insulation Resistance : 500M $\Omega$  Min.  
 Contact Resistance : 30m $\Omega$  Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

**PART NO : 53A88-B\*1**

Positions  
 Contacts  
 Housing Color  
 B : Black

Ports  
 Gold Plated  
 1 : 90"  
 2 : 150"  
 3 : 300"  
 4 : 500"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 53 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	
(B)					
(C)					
(D)					
(E)					

**TOLERANCE(公差) :**  
 0.000 mm  $\pm$  0.075 mm  
 0.00 mm  $\pm$  0.15 mm  
 0.0 mm  $\pm$  0.25 mm

TITLE		NON-SHIELDED RJ45 TOP ENTRY PCB JACK		UNIT
圖名		NON-SHIELDED RJ45 TOP ENTRY PCB JACK		mm
PART NO.		53A88-B*1		inch
REV. 料號		DATE		SCALE
A.1		2007-05-09		1:1
CHECKED BY		DRAWN BY		比例
審核		Michael		Valiant
		製圖		



**博 崙 電 子 股 份 有 限 公 司**  
**POWERWAY ELECTRONICS CO.,LTD.**