



Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 4 6 6 - B * 2

Positions →
 Contacts →
 Ports →
 Gold Plated

Housing Color →
 0 : Gold Plated
 1 : 60"
 2 : 150"
 3 : 300"
 4 : 500"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 54 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE		NON-SHIELDED RJ11		UNIT
圖名		SIDE ENTRY PCB JACK		單位
PART NO.		5466-B*2		SCALE
料號				比例
REV.	DATE	DATE	DATE	比例
版本	日期	日期	日期	比例
CHECKED BY	審核	DRAWN BY	製圖	比例
	A.1	2007-09-22		1:1
	Michael	David		

PW 博 威 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.