



**Electrical Characteristics :**  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 50mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing: Thermoplastic UL 94V-0  
 Contact : Selective Gold Plating  
 Terminal: 0.35mm Thickness Phosphor Bronze  
 Plated With Gold And Tin In Solder Area.  
 CUL File No : E215573

**PART NO : 8 1 8 8 D N - B \* 2 \* - 0**

Positions  
 Contacts  
 Ports  
 Led Options  
 Gold Plated  
 0 : Gold Plated  
 1 : 6U"  
 2 : 15U"  
 3 : 30U"  
 4 : 50U"

Housing Color  
 B : Black

**LED Color Options Table**

LED Color Options	LED 2 (Left)	LED 1 (Right)	LED DASH OPTION
No LED	No LED	No LED	0
Yellow	Green	Green	1
No LED	Green	No LED	2
Yellow	Yellow	No LED	3
Green	Green	Yellow	4
Green	Yellow	Green	5
Yellow	Yellow	Yellow	6
Orange/Green	Orange/Green	Orange/Green	7
Yellow/Green	Yellow/Green	Yellow/Green	8
Orange/Green	Yellow	Yellow	9
No LED	Green/Yellow	Green/Yellow	Z
Green	Orange	Orange	A
Orange	Green	Green	B
Green	Red	Red	C
Red	Green	Green	D



**博 崙 電 子 股 份 有 限 公 司**  
**POWERWAY ELECTRONICS CO.,LTD.**

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 81 (SERIES)	TITLE	UNIT
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick		NON-SHIELDED RJ45 WITH LED PCB JACK	mm
(B)							inch
(C)							SCALE 1:1
(D)							
(E)							

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

PART NO.	SCALE
8188DN-B*2*-0	1:1

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

**TOLERANCE(公差):**  
 0.000 mm ± 0.075 mm  
 0.00 mm ± 0.15 mm  
 0.0 mm ± 0.25 mm

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael

  

REV.	DATE	CHECKED BY	DRAWN BY
A.1	2007-03-22	Michael	Michael