


Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573



ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)
①	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	
②					
③					
④					
⑤					

TOLERANCE(公差) :
 0.000 mm ± 0.075 mm
 0.00 mm ± 0.15 mm
 0.0 mm ± 0.25 mm

 博 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD.		TITLE	NON-SHIELDED RJ45	UNIT	mm
		圖名	SIDE ENTRY PCB JACK	單位	Inch
PART NO.	8208-B*1	SCALE	1:1		
REV.	A.1	DATE	2007-01-26		
版本	日期				
CHECKED BY	Michael	DRAWN BY	Valiant		
審核		製圖			