


**Electrical Characteristics :**  
 Insulation Resistance : 500MQ Min.  
 Contact Resistance : 30mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

**PART NO : 8 2 0 8 - B \* 2**

Positions →  
 Contacts →  
 Ports →  
 Gold Plated  
 0 : Gold Flash  
 1 : 8u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"  
 Housing Color  
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	NICK	TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

 <b>博 崑 電 子 股 份 有 限 公 司</b> <b>POWERWAY ELECTRONICS CO.,LTD.</b>		TITLE	NON-SHIELDED RJ45	UNIT	mm
		圖 名	SIDE ENTRY PCB JACK	單位	inch
PART NO.	8208-B*2	SCALE	1:1		
料 號		比 例			
REV.	A.1	DATE	2007-03-05		
版 本		日期			
CHECKED BY	Michael	DRAWN BY	Valiant		
審 核		製 圖			