

SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 Shield : Brass, Nickel Plating.
 CUL File No : E215573


PART NO : 8 2 8 8 S - B * 2 5 - R

Positions →
 Contacts →
 Panel Ground →
 S : 3 Sides With Panel Ground
 Housing Color →

Ports
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.
A	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick
B				
C				
D				
E				

FILE NO : 82 (SERIES)
TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm

 博 歲 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD.		TITLE	SHIELDED RJ45	UNIT	mm
		圖 名	SIDE ENTRY PCB JACK	單位	inch
PART NO.	8288S-B*25-R	SCALE	1:1		
REV.	A.1	DATE	2007-01-29		
CHECKED BY	Michael	DRAWN BY			Valiant
審 核		製 圖			