



Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 30m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 8 3 0 8 - B * 1

Positions →
 Contacts →
 Gold Plated
 0 : Gold Plated
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

Housing Color →
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 83 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

PW 博 威 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.

TITLE	NON-SHIELDED RJ45 SIDE ENTRY PCB JACK	UNIT	mm
PART NO.	8308-B*1	SCALE	1:1
REV. 料號	A.1	DATE	2007-03-09
REV. 版本	A.1	DATE	2007-03-09
CHECKED BY 審核	Michael	DRAWN BY 製圖	Valiant