



**Electrical Characteristics :**  
 Insulation Resistance : 500M $\Omega$  Min.  
 Contact Resistance : 30m $\Omega$  Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

**PART NO : 8 3 8 6 B - B\*1 S**

Positions →  
 Contacts →  
 Housing Color →  
 B : Black

For RU11  
 Ports  
 Gold Plated  
 0 : Gold Flash  
 1 : 6u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 83 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

**PW** 博 威 電 子 股 份 有 限 公 司  
 POWERWAY ELECTRONICS CO.,LTD.

TITLE	NON-SHIELDED RJ11 SIDE ENTRY PCB JACK	UNIT	mm
PART NO.	8386B-B*1S	SCALE	1:1
REV. 料號	A.1	DATE 日期	2007-06-14
CHECKED BY 審核	Michael	DRAWN BY 製圖	Valiant