


Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 50m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 8 3 8 6 C - B * 1 S

Positions →
 Contacts →
 For RJ11
 Ports
 Gold Plated
 0 : Gold Flash
 1 : 6 μ "
 2 : 15 μ "
 3 : 30 μ "
 4 : 50 μ "
 Housing Color
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 83 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm \pm 0.075 mm 0.00 mm \pm 0.15 mm 0.0 mm \pm 0.25 mm
(B)					
(C)					
(D)					
(E)					

 **博 崙 電 子 股 份 有 限 公 司**
POWERWAY ELECTRONICS CO.,LTD.

TITLE	NON-SHIELDED RJ11	UNIT
圖名	SIDE ENTRY PCB JACK	mm
PART NO.	8386C-B*1S	inch
料號		SCALE
REV. 版本	A.1	日期
CHECKED BY 審核	Michael	DATE
		2007-07-17
	DRAWN BY	製圖
	Michael	Valiant