



Electrical Characteristics :
 Insulation Resistance : 500MQ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:

Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 8508-B*2

Positions →
 Contacts →
 Ports →
 Gold Plated
 Housing Color →
 B : Black

1 : 6U"
 2 : 75u"
 3 : 30u"
 4 : 50u"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 85 (SERIES)
Ⓐ	A.1	Withstand Voltage 500V修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
Ⓑ					
Ⓒ					
Ⓓ					
Ⓔ					

PW 博 威 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.

TITLE	NON-SHIELDED RJ45	UNIT
圖名	2 PORTS SIDE ENTRY PCB JACK	mm
PART NO.	8508-B*2	inch
料號		SCALE
REV. 版本	A.1	日期
CHECKED BY 審核	Michael	2007-02-26
		DRAWN BY 製圖
		Valiant