


Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 30m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 Shield : Brass, Nickel Plating.
 CUL File No : E215573

PART NO : 8508S-B*2*

Positions
 Contacts
 Housing Color
 B : Black

Gold Plated
 0 : Gold Flash
 1 : 8u"
 2 : 15u"
 3 : 30u"
 4 : 50u"



PW 博 歲 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick
(B)				
(C)				
(D)				
(E)				

FILE NO : 85 (SERIES)
 TOLERANCE (公差) :
 0.000 mm \pm 0.075 mm
 0.00 mm \pm 0.15 mm
 0.0 mm \pm 0.25 mm

TITLE	SHIELDED RJ45		UNIT	mm
圖名	SIDE ENTRY PCB JACK		單位	Inch
PART NO.	8508S-B*2*		SCALE	1:1
料號			比例	
REV.	A.1	DATE	2008-05-23	
版本	日期			
CHECKED BY	Michael	DRAWN BY	Michael	Maisie
審核	製圖			