



SUGGESTED PCB LAYOUT  
TOP VIEW

**Electrical Characteristics :**  
 Insulation Resistance : 500M  $\Omega$  Min.  
 Contact Resistance : 50m  $\Omega$  Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 Shield : Brass, Nickel Plating.  
 CUL File No : E215573

**PART NO : 8 2 8 8 - B \* 4 5 - R**

Positions →  
 Contacts →  
 Housing Color →

Ports  
 Gold Plated  
 0 : Gold Flash  
 1 : 6u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)
Ⓐ	A.1	Withstand Voltage 500修改為 1000VAC	2008-08-01	Nick	TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
Ⓑ					
Ⓒ					
Ⓓ					
Ⓔ					

**PW** 博 歲 電 子 股 份 有 限 公 司  
 POWERWAY ELECTRONICS CO.,LTD.

TITLE	DOUBLE ROW SHIELDED RJ45 SIDE ENTRY PCB JACK	UNIT	mm
圖名	DOUBLE ROW SHIELDED RJ45 SIDE ENTRY PCB JACK <td>單位</td> <td>mm</td>	單位	mm
PART NO.	8288-B*45-R <td>SCALE</td> <td>1:1</td>	SCALE	1:1
料號	8288-B*45-R <td>比例</td> <td>1:1</td>	比例	1:1
REV.	A.1	DATE	2007-05-23
版本	A.1	日期	2007-05-23
CHECKED BY	Michael	DRAWN BY	Valiant
審核	Michael	製圖	Valiant